

LIGHTWAVE- lightwaveglobal

Technical Data Sheet

Model		LW-CH-L-65W
Specification		Shell: PC
Power Rating VA		100-240V ~
Input	Voltage Range	100-240V
	Frequency	50/60Hz 1.5A Max
Output	Voltage (inverter Mode)	Directly charge
	Capacity	C1 PD OUTPUT:5V/3A,9V/3A,12V/3A, 15V/3A, 20V/3.25A 65W Max C2 PD OUTPUT:5V/3A,9V/3A,12V/3A, 15V/3A, 20V/3.25A 65W Max C3 OUTPUT: 5V/3A,9V/3A,12V/3A, 15V/3A, 20V/3.25A 65W Max C1+C2=45W+20W 65W Max C1+C3=45W+20W Max C2+C3=5V/3.6A 18W Max TOTAL POWER: 65W Max
	Waverform Over/Under Volt.	Over Voltage Protect
Protection	Spike and Surge Suppression	this items don't have surge suppression
	Over/ Under Voltage	overload protection
	Over Load/Short Circuit	short circuit protection
Battery	Type	no have
	Recharge Time	no have
	Backup Time(Depend on Load)	no have
Physical	Weight(kgs)	0.304kg
	Shipping weight(kgs)	0.404kg
	Dimension (mm)	74*51*34
Efficiency	AC-AC	
	DC-AC	
Acoustic	Noice Level	the best low level

Environmental	Temperature	depends on the local city to write
	Humidity	depends on the local city to write
Power Outlets	NO. and types	